

Sanders

Flood light Range



Specifications

1lt and 2lt 12W LED Security flood light
LED
Single head or twin head version available
Colour Temperature 5700K Daylight
IP44, CRI 80

Available in:

- PAR38 Security Floodlight
- PAR38 Security Floodlight with PIR Sensor



Dimensions

MXD6612BLK & MXD6612BLK-SEN
Base: L12.0 x W11.0 x H3.5cm
Lampholder: L5.8 x W5.8 x H7.0cm
Sensor(when applicable): L5.8 x W7.0 x H4.7cm
Inner qty: 4
Inner: (58x14.5x34)cm
Outer: (60x31x70)cm

MXD6624BLK & MXD6624BLK-SEN
Base: L12.0 x W11.0 x H3.5cm
Lampholder: L5.8 x W5.8 x H7.0
Sensor(when applicable): : L5.8 x W7.0 x
H4.7cm
Outer qty: 6
Outer: (55x18x57)cm



LED
Included



Motion
Sensor

IP44
Rating

Model No.	Description	Colour	Globe
MXD6612BLK	1lt PAR38 Security Floodlight	BLK	1*12W 1200lm
MXD6624BLK	2lt PAR38 Security Floodlight	BLK	2*12W 1200lm
MXD6612BLK-SEN	1lt PAR38 Floodlight W Sensor	BLK	1*12W 1200lm
MXD6624BLK-SEN	2lt PAR38 Floodlight W Sensor	BLK	2*12W 1200lm